SECONDARY LITHIUM CELLS FOR SPACE APPLICATIONS

JPL

S. SURAMPUDI, D. H. SHEN, C.-K. HUANG,
S. R. NARAYANAN, A. ATTIA, G. HALPERT

1991 NASA Aerospace Battery Workshop
U. S. Space and Rocket Center
Huntville, AL
October 29-31, 1991

JPL

SECONDARY LITHIUM CELLS/BATTERIES
OUTLINE

(1) JPL PROGRAM GOAL

(2) SPACE APPLICATIONS

(3) JPL PROGRESS

(4) SUMMARY

(5) ACKNOWLEDGEMENTS

JPL

SECONDARY LITHIUM CELLS/BATTERIES
PROGRAM GOAL

- DEMONSTRATE THE FEASIBILITYOF AMBIENT TEMPERATURE SECONDARY LITHIUM CELL TECHNOLOGY BY 1994

- TARGETS
  - 100 Wh/kg
  - 1000 CYCLES (50% DOD)
  - 5 YEAR ACTIVE STORAGE LIFE
  - SAFE

JPL

SECONDARY LITHIUM CELLS/BATTERIES
ADVANTAGES

- 3-4 FOLD INCREASE IN SPECIFIC ENERGY AND ENERGY DENSITY OVER Ni-Cd
- LOW SELF DISCHARGE
- LONG ACTIVE SHELF LIFE

JPL

ADVANCED RECHARGEABLE BATTERY PERFORMANCE ENVELOPE



JPL

RECHARGEABLE LITHIUM CELL PROGRAM
PROJECTED APPLICATIONS

PLANETARY ORBITERS (MERCURY ORBITER)



MISSIONS TO COMETS (COMET NUCLEUS SAMPLE RETURN TAIL PROBE)



MARS ROVER

PENETRATORS (GLOBAL NETWORK MISSION)

JPL

CLASSIFICATION OF SECONDARY LITHIUM CELLS



JPL

SECONDARY LITHIUM CELLS/BATTERIES

SPECIFIC ENERGY OF SELECTED CATHODE MATERIALS

MATERIAL	AVE. V (Volt)	Li EQ.* PER mole	SPECIFIC ENERGY (Wh/kg) THEO.	EXP.**	CYCLE LIFE
JPL STUDIES (EXPERIMENTAL CELLS)					
$Li\text{-}TiS_2$	2.1	0.9	473	417	300+
MoS_2	1.9	2.0	717	421	50+
$NbSe_3$	1.8	2.8	412	384	150+
V_6O_{13}	2.2	4.0	636	361	50+
FROM LITERATURE (PROTOTYPE CELLS)					
$Li\text{-}TS_2$	2.1	0.8	473	378	200+
$NbSe_3$	1.8	2.5	412	330	200+
MoS_2	1.7	0.8	272	214	200+
MnO_2	3.0	0.5	855	364	200+
CoO_2	4.0	0.5	1094	465	50+
$CuCl_2$	3.2	2.0	1125	665	140+
SO_2	3.1	1.0	524	524	30+

* EXPERIMENTALLY REVERSIBLE

** EXPERIMENTALLY REVERSIBLE LITHIUM EQ./mole, BINDER AND CONDUCTING DILUENTS WERE TAKEN INTO CONSIDERATION

RECHARGEABLE AMBIENT-TEMPERATURE LITHIUM BATTERIES

JPL

SCHEMATIC DIAGRAM OF A Li-TiS_2 CELL



CELL REACTIONS

DISCHARGE . . LI INTERCALATION (INSERTION)

CHARGE. . . . . LI DE-INTERCALATION (REMOVAL)

$$LI + TiS_2 \underset{C}{\overset{D}{\rightleftharpoons}} LI\text{-}TiS_2$$

ELECTROLYTE

LITHIUM ARSENIC HEXAFLUORIDE ($LiAsF_6$) – SALT

2-METHYL TETRA HYDROFURAN (2-MeTHF) WITH

ETHYLENE CARBONATE (EC) – MIXED SOLVENT


TYPICAL CHARGE/DISCHARGE CURVE FOR 1 Ah Li-TiS2 CELL
VOLTS
2.5
2.4
2.3
2.2
2.1
2
1.9
1.8
1.7
1.6
0
100
200
300
400
500
600
700
800
900
1000
ELAPSED MINUTES
176MA DISCHARGE
88MA CHARGE

END-OF-DISCHARGE VOLTAGE VS CYCLES FOR JPL FABRICATED LITHIUM-TITANIUM DISULFIDE CELLS



ETC-22.XLC

DEP 9/23/91 1:56 PM

CYCLE LIFE PERFORMANCE OF 1 AHR LITHIUM-TITANIUM DISULFIDE CELLS WITH VARIOUS ELECTROLYTES



ETC-25.XLC

DEP 10/23/91 9:58 AM

C/5 PERFORMANCE (200MA) OF AA 1 AMPERE-HOUR LITHIUM TITANIUM DISULFIDE CELL



ETC-10.XLC

DEP 9/9/91 3:39 PM



ETC-8.XLC

DEP 9/9/91 3:20 PM

PERFORMANCE OF A TYPICAL MANUFACTURED AA 1 AMPERE-HOUR LITHIUM TITANIUM DISULFIDE CELL



ETC-13.XLC

DEP 9/9/91 4:56 PM


CYCLE LIFE CHARACTERISTICS OF JPL 1 Ah Li-TiS2 CELL
AT 100% DOD
AHRS
1.6
1.4
1.2
1
0.8
0.6
0.4
0.2
0
0
50
100
150
200
250
300
350
100% DOD CYCLES

JPL

REQUIRED TECHNOLOGY IMPROVEMENTS

IPARAMETER	PRESENT STATUS	NASA REQUIREMENT
CYCLE LIFE	335+ (100% DOD) 650+ (50% DOD)	500 (100% DOD) 1000 (50% DOD)
RATE CAPABILITY	C/5	C/2
CELL SIZE	1 Ah	30 Ah
OVERCHARGE/OVERDISCHARGE	SENSITIVE	TOLERANT
ACTIVE STORAGE	1 YEAR	5 YEARS

RECHARGEABLE LITHIUM CELL PROGRAM

JPL ADVANCES IN Li-TiS_2 CELL TECHNOLOGY



JPL

ALTERNATE Li ANODE MATERIAL STUDIES

EXPERIMENTAL EVALUATION OF SELECTED Li ALLOYS

Material	Stability*	Ave. E vs. Li (mV)	Reversibility** # OF Li		Specific Energy*** (wh/Kg)	
			Estimated	Experimental	Estimated	Experimental
$Li_{1.2}Al$	good	380	1.0	< 0.8	312	300
$Li_{2.85}Cd$	poor	0	2.6	--	322	--
$Li_{4.5}Pb$	good	388	3.5	< 1.5	254	167
$Li_{0.15}C$	good	200	0.15	< 0.08	255	186
$Li_{4.4}Si$	poor	--	--	--	--	--
$Li_{4.3}Sn$	good	411	2.0	< 1.0	243	171
$Li_{1.1}Zn$	good	191	0.6	< 0.12	220	62

* Microcalorimetric and OCV measurements.

** Galvanostatic cycling studies.

*** Calculated based on TiS2 cathode.

SUMMARY OF FINDINGS:

- Li-Si & Li-Cd ALLOYS WERE FOUND TO BE UNSTABLE.
- SELECTED Li-Al and Li-C ALLOY SYSTEMS FOR DETAILED ASSESSMENT.

JPL

ELECTROCHEMICAL INTERCALATION & DE-INTERCALATION OF Li IN Li_xC



JPL

COMPARISON OF CHARGE & DISCHARGE CHARACTERISTICS OF 1 Ah & 32 mAh CELLS





JPL

REDOX SHUTTLE APPROACH TO OVERCHARGE PROTECTION



CHEMICAL ENERGY CONVERSION (BATTERY) TECHNOLOGY

JPL RECHARGEABLE LITHIUM CELL PROGRAM

STUDIES ON OVERCHARGE PROTECTION



⌐CONDARY LITHIUM CELLS/BATTERIES

CONCLUSIONS

- SECONDARY LITHIUM BATTERIES ARE SUITABLE FOR PLANETARY MISSIONS REQUIRING
  - HIGH SPECIFIC ENERGY
  - LONG ACTIVE SHELF LIFE
  - LIMITED CYCLE LIFE
- TiS_2 CATHODE MATERIAL MEETS ALL REQUIREMENTS FOR RECHARGABLE Li CELL
  - HIGH INTRINSIC REVERSIBILITY
  - REALIZABLE SPECIFIC ENERGY
- SECONDARY LITHIUM TECHNOLOGY IS STILL EVOLVING
  - LOW CAPACITY CELLS (~1 Ah) DEMONSTRATED
  - > 700 CYCLES (@ 50% DOD) ACHIEVED
- WORK IS IN PROGRESS TO IMPROVE CYCLE LIFE AND SAFETY
  - ELECTROLYTES
  - ALTERNATE Li ANODE
  - SEPARATORS

SECONDARY LITHIUM CELLS/BATTERIES

ACKNOWLEDGEMENTS

THIS WORK DESCRIBED HERE WAS CARRIED OUT AT THE JET PROPULSION LABORATORY, CALIFORNIA INSTITUTE OF TECHNOLOGY, THROUGH AN AGREEMENT WITH THE NATIONAL AERONAUTICS AND SPACE ADMINISTRATION. (Code RP)